




Structural Vinyl Porch Post

Recessed Panel, Manchester, Plain, Vintage
Madison, Lexus, Traditional, & Heritage



Note: not intended for free standing structures

Recommended Tools

- Safety Glasses
- Tape Measure & Pencil
- Power Drill w/ 1/8" bit
- Mitre Saw

What's Included

- (1) Vinyl Porch Post
- (1) Aluminum Support Beam (*not incl. w Hollow Posts*)
- (2) Mounting Plates (*per Post*)
- (2) Trim Covers (*optional*)
- (8) #14 x 1 1/2" Flat head S.S. screws
- (4) #14 x 1 3/4" Tapcon screws
- (4) #10 x 2 1/4" Colored screws

- *These directions are only a guide and may not address every situation.*
- *Always wear proper safety equipment while assembling and installing.*
- *The installer should obtain all required building permits and follow all installation procedures in accordance with applicable building code requirements.*
- *Superior Plastic Products, Inc. shall not be held liable for improper or unsafe installations.*
- *Applying paint, will void your warranty.*
- *To ensure proper coverage by our warranty please visit our website and complete the warranty form and mail to: Superior Plastic Products, Inc., 260 Jalyn Drive, New Holland, PA 17557*


260 Jalyn Drive • New Holland, PA 17557

SuperiorPlasticProducts.com

SPPIG161111

Disclaimer: It is the responsibility of the installer to determine the correct dimensions as called out in the building plans for placement of the Posts.



Mark center line of header. Then mark the lateral placement of the Post.



Brace the porch header at the correct height (*refer to building plans*). Using a plumb line; mark the center location on the floor surface.

Note: If installing a railing system; take into account the railing height prior to cutting the Post. Ensure there is enough room to attach the railing mounting brackets on the square section of the Post.

Subtract $\frac{3}{8}$ " from total height between header and floor surface (*thickness of Mounting Plates*). Use this dimension to cut the Posts to length.



42" Rail Height = cut up to 8" off bottom of Post
36" Rail Height = cut up to 14" off bottom of Post

! Cutting Tip

Ensure cut is the same pitch as floor surface. Use Mitre saw with a carbide tipped multi-purpose blade.

Install top and bottom Mounting Plates onto Post. Then Slide a Trim ring onto both ends of the Post (*if utilized*).

Note: Prior to the next step raise the header $\frac{1}{8}$ " (*at individual location only*).

Position Post and Fasten the Mounting Plate by rotating the Post slightly. Repeat for top and bottom Mounting Plates. (**use correct screws for application*).

- * Top & Bottom Plate (wood surface): #14 x 1½" S.S. screws**
- Bottom Plate (concrete floor): #14 x 1¾" Tapcon screws**

Rotate Post back to neutral position and lower header. (*do not remove braces until all Posts have been installed*)

Install Hold Down Screws

Measure $\frac{5}{8}$ " on Center line of two opposing faces. Drill a $\frac{1}{8}$ " hole through the Post, Structural Support Beam, and Mounting Plate. Then fasten with #10 x 2¼" colored screws.

